V7 PD 611X

DLP Projector Line

Specifications

PRODUCT SPECIFICATIONS	
Technology	Single 0.55” DLP Panel
Projection System	DLP
Brightness	2000 ANSI max. 1800 ANSI typ.
Weight	2.3 kg
Native Resolution	1024 x 768 XGA
Aspect Ratio	4:3, supports 16:9
Video Compatibility	NTSC, PAL, SECAM, HDTV/Component (via VGA)
Computer Compatibility	XGA, resized: VGA, SVGA, SXGA
Input Source	VGA, S-Video, Composite-Video
Rear Projection	yes
Regulatory/Standards	CE, GS, UL, FCC, CCC, CB

OPTICAL SPECIFICATIONS	
Displayable Colours	16.7 Mio.
Contrast Ratio	2000:1 (on/off)
Brightness Uniformity	80%
Lamp Type	200 Watt Ushio
Lamp Life	2000 hours
Projection Lens	18 - 21.57 mm
Zoom Ratio	1:1.2
Projection Screen Size	0,792 - 7,92 m (diagonal)
Throw Distance	1.2 - 10 m

ELECTRICAL SPECIFICATIONS	
Horizontal Scan Rate	31 - 79 kHz
Vertical Scan Rate	50 - 85 Hz
Pixel Rate	108 MHz

MECHANICAL SPECIFICATIONS	
Dimensions WxHxD	254 x 102 x 202 mm
Ceiling mountable	yes
Audible Noise	36 dBA, ECO mode: 34 dBA
Power Supply	AC 100-240 V, 50-60 Hz
Power Consumption	250 Watt max., ECO mode: 210 Watt max.
Keystone Correction	vertical: +/- 20°
Audio	1x 2 Watt speaker
SUPPLIED ACCESSORIES	Manua, Power Cord, VGA-, Composite Video, S-Video and Audio Cable, IR Remote Control, Soft Bag
SERVICE	Projector: 3 years Pick-Up / Lamp: 90 days

The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7 Videoseven. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions are disclaimed. Measurement standards and testing conditions as per manufacturer definitions, available on request.
Issue: 11/2005

V7® DISPLAYS FOR you

VIDEOSEVEN